



**Meets ANSI/ESD S20.20 and Packaging standard ANSI/ESD S541**

**Features**

- Constructed from extruded honey-comb structure of high impact polypropylene material yielding superior strength and durability
- Provides physical protection with conductive material ensuring reliable path-to-ground
- Rolled over side construction (double thickness) for greater durability
- Identified with ESD protective symbol as required by ANSI/ESD S541
- Conductive plastic handle for ease of handling
- Includes steel wire frame for extra strength
- Chemical and moisture resistant
- Ideal use where corrugated and/or paper products cannot be used
- Product ships assembled
- Available options include: (1) Lid manufactured from Endura-Tek<sup>®</sup>; (2) Static Dissipative Foam bottom to provide ESD and shock protection
- Made in the United States of America

**Specifications**

**Physical Properties**

	<b>Typical Values</b>
Resin Type	Polypropylene
Conductive	Inherently
Material Thickness	4.0 mm
Melting Temperature	320° F
Heat Deflection	185° F

Properties	Standard Requirements	Typical Range	Testing Method
Surface Resistance	< 1 x 10 <sup>4</sup> ohms (Conductive Packaging)	< 1 x 10 <sup>4</sup> ohms	ANSI/ESD STM11.11

Part No.	Size I.D. - L x W x D (IN)	Size I.D. - L x W x D (MM)	Lid**	Foam**
<a href="#">39440</a>	17 x 13 x 6-3/4	432 x 330 x 171	<a href="#">39470</a>	<a href="#">37452</a>
<a href="#">39441</a>	17 x 13 x 8-3/4	432 x 330 x 222	<a href="#">39470</a>	<a href="#">37452</a>
<a href="#">39442</a>	17 x 13 x 10-3/4	432 x 330 x 273	<a href="#">39470</a>	<a href="#">37452</a>
<a href="#">39443</a>	18-3/8 x 12-3/8 x 12-3/4	467 x 314 x 324	<a href="#">39471</a>	<a href="#">37454</a>
<a href="#">39444</a>	18-5/8 x 15 x 5-7/8	473 x 381 x 149	<a href="#">39472</a>	<a href="#">37455</a>
<a href="#">39445</a>	18-5/8 x 15 x 8	473 x 381 x 203	<a href="#">39472</a>	<a href="#">37455</a>
<a href="#">39446</a>	22-7/8 x 12-7/8 x 8	581 x 327 x 203	<a href="#">39473</a>	<a href="#">37453</a>
<a href="#">39447</a>	22-7/8 x 12-7/8 x 18-1/4	581 x 327 x 464	<a href="#">39473</a>	<a href="#">37453</a>

\*\* Lid and foam pad are sold separately  
Unless otherwise noted, tolerances are ± 1/8"



Made in the United States of America

Per Packaging standard ANSI/ESD S54.1 section 6.1. Inside an ESD Protected Area "Packaging used within an EPA (that satisfies the minimum requirements of ANSI/ESD S20.20) shall be:

1. Low charge generation.
2. Dissipative or conductive materials for intimate contact."

Specifications and procedures subject to change without notice.

**ENDURA-TEK<sup>®</sup> STORAGE CONTAINERS**

**PROTEKTIVE PAK**

**PROTEKTIVE PAK**  
13520 MONTE VISTA AVENUE, CHINO, CA 91710  
PHONE (909) 627-2578  
[ProtektivePak.com](http://ProtektivePak.com)

**DRAWING NUMBER**  
39440

**DATE:**  
January  
2026